





#### The Source Book

#### PRODUCTION CONTACT INFORMATION

# **Ad Management Services**

Los Angeles, CA USA Phone: +1 310 445 3766 Fax: +1 310 362 8808

# Ad Materials FTP, Email, or Send to:

**UBM Canon** Attention: EMDT AMS 11444 W. Olympic Blvd. Los Angeles, CA 90064-1549 USA

For more information visit www.ubmcanon.com • www.canonmediakit.com • www.canonespecs.com

#### DIGITAL A D SPECIFICATIONS

We require digital files. Acceptable formats are: PDF, EPS, TIFF or a Postscript file. Files should be 300 dpi, CMYK, Grayscale, or Two-Color with fonts and images embedded. Any placed images should be at 100%, 300 dpi, and CMYK or Grayscale. Please do not submit native application files such as Quark, Illustrator, etc. Illustrator EPS files are acceptable if fonts are outlined and all images are embedded at 300 dpi.

FTP: UBM Canon has an FTP server available for your use when uploading advertising materials to European Medical Device Technology. For directions on accessing the FTP server, including IP address and current passwords, as well as usage tips, visit canonespecs.com. Compress your files by using Stuffit or Winzip to shrink large files and to protect from corruption. Color proofs should be mailed within one day of the FTP upload.

Email: Files can be emailed to us if they are 5 MB or smaller. Email should state publication name, issue number, advertiser name, contact name and contact telephone number. Compress your files by using Stuffit or Winzip to shrink large files and to protect from corruption. Color proofs should be mailed within one day of sending email. See canonespecs.com for email address.

Acceptable Media: We prefer you upload your ad to our FTP server or send it via email (see above), but you may also send your ad on CD. Please include a SWOP approved Iris, Kodak etc. proof of your ad from the file submitted. Clearly label your disc with advertiser name, issue number, ad headline, contact name and contact telephone number.

Binding: Perfect bound

submitted file.

Preflight: All digital ads undergo a

agency will be notified immediately.

A corrected digital ad file must be resubmitted and accompanied by a

new proof, and written instructions

to replace and purge the previously

preflight inspection process. If an error is detected, the advertiser or

## **Screen Requirements:**

2 - color 120 line, 133 maximum

4 - color 133 line, 150 maximum.

#### Density:

2 - color 185% maximum

4 - color process 300% maximum

Bleeds: Allow 1/8" on all sides. Keep live matter %" from trim, head, foot and binding edge. Keep crop marks outside of live area.

Trim Size: 226mm x 276mm

(8.88" x 10.88")

# **Ad Space Units** 2 Page Spread

# **Bleed**

457mm x 283mm 18" x 11.13" (live area not to exceed 438mm x 264mm/17.25" x 10.38")

#### 2 Page Spread Non-bleed

438mm x 264mm 17.25" x 10.38"

# 2/3 Page Horizontal

195mm x 165mm 7.68" x 6.5"


### **Full Page**



Bleed: 232mm x 283mm 9.13" x 11.13" (live area not to exceed nonbleed size centered)


Non-Bleed: 213mm x 264mm 8.38" x 10.38"

## 2/3 Page Vertical



126mm x 255mm 4.96" x 10.04"


#### 1/2 Page



Vertical: 93mm x 255mm 3.66" x 10.04"


Horizontal: 195mm x 123mm 7.68" x 4.84"

#### 1/2 Page Island



126mm x 165mm 4.96" x 6.5"

#### 1/3 Page




Vertical 60mm x 255mm 2.36" x 10.04"

Horizontal: 7.68" x 3.15"

Square: 126mm x 123mm

#### 1/4 Page



1/4 Page 93mm x 123mm 3.66" x 4.84"

195mm x 80mm

4.96" x 4.84"